



## TIMBERDUC® PUR 533 SE




Special suction and transport hose in flame-retardant polyurethane resistant to aggressive wood types and wood preservatives, especially suitable:

- for the suction of wood dust and wood chips on wood processing machines
- for abrasive solids such as dust, powder, fibres, chips and granulates
- for de-dusting and suction plants

### Hose construction

1. spring steel wire firmly embedded in wall
  2. profile with optimised flow properties
- wall: premium polyurethane, resistant to aggressive wood types and wood preservatives, with flame-retardant additive (Pre-PUR®)
3. wall thickness 0.7 mm approx.



- heavy model
- highly abrasion-proof
- smooth interior
- optimized flow properties
- flexible

### According to

- German TRBS 2153 (formerly BGR 132): capable of electro-static discharge by grounding the spiral

### Temperature range

-40°C ÷ +90°C, with peaks up to +125°C

No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
533-0040-5070	40	48	0,420	53	0,350	10
533-0045-5070	45	53	0,385	58	0,380	10
533-0050-5070	50	58	0,365	64	0,420	10 15
533-0060-5070	60	68	0,285	75	0,490	10
533-0065-5070	65	73	0,255	80	0,530	10
533-0070-5070	70	79	0,210	87	0,560	10
533-0075-5070	75	84	0,195	92	0,600	10
533-0076-5070	76	85	0,190	93	0,650	-
533-0080-5070	80	89	0,175	98	0,630	10 15
533-0090-5070	90	99	0,155	109	0,710	10
533-0100-5070	100	109	0,120	120	0,780	10 15
533-0102-5070	102	111	0,120	122	0,990	-
533-0110-5070	110	119	0,110	131	0,860	10
533-0115-5070	115	124	0,105	136	1,110	-
533-0120-5070	120	129	0,105	142	0,930	10 15
533-0125-5070	125	134	0,085	147	0,970	10
533-0127-5070	127	136	0,085	148	1,220	-

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses



No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
<b>533-0130-5070</b>	130	139	0,085	153	1,000	<b>10</b>
<b>533-0140-5070</b>	140	149	0,085	164	1,080	<b>10 15</b>
<b>533-0150-5070</b>	150	159	0,075	175	1,370	<b>10 15</b>
<b>533-0152-5070</b>	152	161	0,075	177	1,540	-
<b>533-0160-5070</b>	160	169	0,065	186	1,460	<b>10 15</b>
<b>533-0170-5070</b>	170	179	0,065	195	1,540	-
<b>533-0175-5070</b>	175	184	0,055	202	1,590	-
<b>533-0180-5070</b>	180	189	0,055	208	1,630	<b>10</b>
<b>533-0200-5070</b>	200	209	0,055	230	1,810	<b>10 15</b>
<b>533-0203-5070</b>	203	212	0,055	233	2,030	-
<b>533-0225-5070</b>	225	234	0,040	257	2,030	10
<b>533-0250-5070</b>	250	259	0,020	285	2,250	10
<b>533-0254-5070</b>	254	263	0,020	290	2,290	-
<b>533-0275-5070</b>	275	284	0,020	312	2,470	-
<b>533-0280-5070</b>	280	289	0,020	318	2,510	10
<b>533-0300-5070</b>	300	309	0,020	340	2,690	10
<b>533-0305-5070</b>	305	314	0,020	345	2,730	-
<b>533-0315-5070</b>	315	324	0,020	356	2,820	10
<b>533-0325-5070</b>	325	334	0,015	367	2,910	-
<b>533-0350-5070</b>	350	359	0,015	395	3,130	10
<b>533-0375-5070</b>	375	384	0,010	424	3,770	-
<b>533-0400-5070</b>	400	409	0,010	450	4,020	10

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses