

## TUBLUESTREAM

Delivery hose suitable for cleaning plant and equipment with hot water mixed with steam.

### Hose construction

**Tube:** EPDM, white, phthalates free, tested in compliance with 1907/2006/CE (REACH). Meets FDA 21 CFR 177.2600, BFR recommendation XXI cat 2, DM 21.03.73 e seguenti, EUROPEAN REGLEMENT 1935/2004/CE, JAPAN-Ministry of Health and Welfare Notice No.370,1959 and No.201,2006, 3A Sanitary Standard Class II.

**Reinforcement:** synthetic plies

**Cover:** smooth, blue, abrasion, ageing, ozone and oil resistant, pin pricked, cloth finish

### Temperature range

-40°C to +164°C



- Suitable for cleaning plant and equipment
- According to FDA 21 CFR 177.2600.
- Working pressure 6bar

Number	ID [mm]	OD [mm]	WP (164°C) [bar]	WP (95°C) [bar]	Burst pressure [bar]	Weight [kg/mt]
IH30240051	10	20	6	20	60	0,29
IH30240052	13	23	6	20	60	0,35
IH30240053	16	26	6	20	60	0,41
IH30240054	19	31	6	20	60	0,60
IH30240055	25	39,5	6	20	60	0,93
	32	46,5	6	20	60	1,16
	<b>38</b>	54	6	20	60	1,47
	<b>51</b>	68	6	20	60	2,03

### Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses