

VOLGA

Hardwall hose used for the suction and delivery of dry cement, sand, gravel, etc.

Hose construction

Tube: black, smooth, antistatic SBR/NR rubber which withstands the passage of abrasive materials.

Reinforcement: high strength synthetic cord, steel helix wire and antistatic copper wire.

Cover: black, smooth (wrapped finish), EPDM rubber, weathering and ozone resistant.

Temperature range

-30°C to +70°C



- Rubber, bulk materials suction and delivery hose, ozone resistant and available with couplings.
- Antistatic
- Working pressure 10bar
- According to ISO 4649: 70 +/- 5mm³.
- Vacuum 0,9 bar

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Bending radius mm	Vacuum bar	Max length m
IH36923100	51	65	10	30	2,07	230	0,9	120
IH36923105	76	92	10	30	3,28	360	0,9	120
IH36923102	102	120	10	30	5,15	450	0,9	120
IH36923107	127	147	10	30	6,71	675	0,9	60
1112490	152	177	10	30	11,81	900	0,8	60

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses